

Stainless steel HMI

Extreme durability. High endurance.

Features	IT1107WX	IT112TX / IT112TY
Display Size	7"	12,1"
Display Technology	TFT	
Display Colors	65 K	
Display Life (hours)	50 K	
Display Backlight	LED	
Display Resolution (pixel)	800 x 480	800x600
Processor	Intel PXA 270	
RAM	64M	128M
Flash	32M	64M
Serial Ports	SPI (232/485/MPI), SP2 (232/485/MPI), CAN, Profibus	
USB Port Host	1 x v 1.1	2 x v 1.1
USB Port Device	1 x v 1.1	2 x v 1.1
Cardbus Slot	1 x Secure Digital	
Compact Flash Slot	-	1 x Compact Flash
Ethernet	1 x 10/100 Mb	2 x 10/100 Mb
Hardware Clock	Supercapacitor 72h	
Consumption (W)	8	15
Power Supply (Vdc)	18 ... 32	
Operating Temperature (°C)	0 ... +50 (non condensing)	
Humidity	<85% (non condensing)	
External Dimensions (W/H/D) (mm)	202 x 142 x 39,2 (58,2 with double port)	336,3 x 256 x 62,9
Cut-out Dimensions (W/H) (mm)	194 x 134	314 x 240
Weight	-2,2	- 4,6
Protection degree (front)	IP69K	
Certifications	CE / EN60068-2-6 / EN60068-2-27 / Humidity EN60068-2-30 / cULus (Certificate no. E189179) EAC / ATEX 2014/34/UE directive Group II Category 3 G D Zone 2/22	