


### Embedded I/O Clack & Play

#### EW600B08B04 8 Digital Input + 4 Digital Output

Supply Voltage (Vdc)	24
Isolation	Optoisolated
Input Numbers	8
Input Type	PNP, NPN
Output Numbers	4
Output Type	PNP (300mA/output)
Operating Temperature (°C)	-10 ... +50 (non condensing)
Storage Temperature (°C)	-20 ... +65
Humidity	<90% (non condensing)
External dimensions (W/H/D/ (mm))	96 x72 x20
Protection Degree	IP 20
Certifications	CE / EN60068-2-6 / EN60068-2-27 / Humidity EN60068-2-30 EAC/ATEX 2014/34/UE directive Group II Category 3 G D Zone 2/22 (mounted on EW100AC)

#### EW600A03A02 3 Analog Inputs + 2 Analog Outputs

Supply Voltage (Vdc)	24
Input Numbers	3
Input Type	0 / 5 V, 0 / 10 V, +10 / -10 V, 0 / 20 mA, 4 / 20 mA
Output Numbers	2
Output Type	0 / 5 V, 0 / 10 V, +10 / -10 V, 0 / 20 mA, 4 / 20 mA
Resolution	16 Bit
Operating Temperature (°C)	-10 ... +50 (non condensing)
Storage Temperature (°C)	-20 ... +65
Humidity	<90% (non condensing)
External dimensions (W/H/D/ (mm))	96 x72 x20
Protection Degree	IP 20
Certifications	CE / EN60068-2-6 / EN60068-2-27 / Humidity EN60068-2-30 EAC/ATEX 2014/34/UE directive Group II Category 3 G D Zone 2/22 (mounted on EW100AC)




## Embedded I/O

### EW600C02N00 2 High Speed Input

Supply Voltage (Vdc)	24
Input Numbers	2
Input Type	Incremental Pulse / Differential Phase (4x) / Up/Down / Pulse + Direction (5-30 Vdc)
Isolation	Optoisolated
Frequency (KHz)	100
Operating Temperature (°C)	-10 ... +50 (non condensing)
Storage Temperature (°C)	-20 ... +65
Humidity	<90% (non condensing)
External dimensions (W/H/D/ (mm))	96 x72 x20
Protection Degree	IP 20
Certifications	CE / EN60068-2-6 / EN60068-2-27 / Humidity EN60068-2-30 EAC/ATEX 2014/34/UE directive Group II Category 3 G D Zone 2/22 (mounted on EW100AC)

### EW600D06N00 6 Thermocouple Input

Input Numbers	6
Input Type	K / J / E / T / N / B / R / S
Resolution (°C)	+ 0,1 / - 0,1
Cold Junction	Internal and External
Operating Temperature (°C)	-10 ... +50 (non condensing)
Storage Temperature (°C)	-20 ... +65
Humidity	<90% (non condensing)
External dimensions (W/H/D/ (mm))	96 x72 x20
Protection Degree	IP 20
Certifications	CE / EN60068-2-6 / EN60068-2-27 / Humidity EN60068-2-30 EAC/ATEX 2014/34/UE directive Group II Category 3 G D Zone 2/22 (mounted on EW100AC)




## Embedded I/O

### EW600E04N00 4 Resistance Thermometer Input

Input Numbers	4
Input Type	Pt100 / Pt200 / Pt500 / Pt1000 / Ni100 / Ni1000
Resolution (°C)	+ 0,1 / - 0,1
Operating Temperature (°C)	-10 .... +50 (non condensing)
Storage Temperature (°C)	-20 ... +65
Humidity	<90% (non condensing)
External dimensions (W/H/D/ (mm))	96 x72 x20
Protection Degree	IP 20
Certifications	CE / EN60068-2-6 / EN60068-2-27 / Humidity EN60068-2-30 EAC/ATEX 2014/34/UE directive Group II Category 3 G D Zone 2/22 (mounted on EW100AC)

### EW600N00C04 4 High Speed Output

Supply Voltage (Vdc)	24
Output Numbers	4
Isolation	Optoisolated
Output Type	CW/CCW - Pulse + Direction 12 - 32VDC push-pull
Output Current (mA)	5 - 10
Resolution (Hz - KHz)	200Hz - 300KHz
Operating Temperature (°C)	-10 .... +50 (non condensing)
Storage Temperature (°C)	-20 ... +65
Humidity	<90% (non condensing)
External dimensions (W/H/D/ (mm))	96 x72 x20
Protection Degree	IP 20
Certifications	CE / EN60068-2-6 / EN60068-2-27 / Humidity EN60068-2-30 EAC/ATEX 2014/34/UE directive Group II Category 3 G D Zone 2/22 (mounted on EW100AC)



## Embedded I/O

### EW600N00E04 4 PWM Output

Supply Voltage (Vdc)	24
Output Numbers	4
Isolation	Optoisolated
Output Type	PWM – 12 – 32 Vdc push-pull
Output Current (mA)	5 - 10
Resolution (Hz - KHz)	200Hz - 300KHz
Operating Temperature (°C)	-10 .... +50 (non condensing)
Storage Temperature (°C)	-20 ... +65
Humidity	<90% (non condensing)
External dimensions (W/H/D/ (mm)	96 x72 x20
Protection Degree	IP 20
Certifications	CE / EN60068-2-6 / EN60068-2-27 / Humidity EN60068-2-30 EAC/ATEX 2014/34/UE directive Group II Category 3 G D Zone 2/22 (mounted on EW100AC)