

Keyboard HMI

Don't touch, just press my keys.

	IT105TK
Display Size	5,7"
Display Technology	Graphic LCD TFT
Display Colors	65.536
Display Backlight	LED
Display Resolution (pixel)	320 x 240
Backlight life (hours)	50 K
Operative keys	18
Function keys	12
Alphanumeric keys	11
Processor	Intel (R) PXA270
RAM (MB)	64
Flash (MB)	32
First Port	SP1 (232/485/MPI)
Second Port	SP2 (RS232/485/MPI), CAN, Profibus-DP
Ethernet	1 x 10/100 Mb
USB Host port	USB 1.1
USB Device port	USB 1.1
Cardbus slot	Secure Digital / MMC
Power Supply (Vdc)	18 - 32
Consumption (W)	~ 10
Operating Temperature (°C)	0 ... +50 (non condensing)
Storage Temperature (°C)	-20 ... + 65
Humidity	<90% (non condensing)
External dimensions(W/H/D) (mm)	261,2 x 172,4 x 51,6 (70,6 with double port)
Cut-out dimensions (W/H) (mm)	243,5 x 147
Weight (kg)	~ 1,5
Protection degree (front)	IP66
Certifications	CE/ cULus/ ATEX 2014/34/UE directive Group II Category 3 G D Zone 2/22 / DNV /Vibration EN60068-2-6 / Shock EN60068-2-27 / Humidity EN60068-2-3