



MONITOR

Industrial Monitor

Endurance and reliability

	XM7W7	XM708	XM712	XM715	XM717	XM719
Display Size	7" wide	8,4"	12,1"	15"	17"	19"
Bezel Aluminum	6mm thickness					
Technology	TFT 262 K colors			TFT 16,2 M colors	TFT 17, M colors	
Display Backlight	LED					
Brightness cd/m2	500	450	370	350	380	400
Contrast	600:1			700:1	1000:1	
Viewing Angle (H-V)	70-60	75-75	140-120			
Lamp life (min at 25°C)	50 K					
Resolution (pixel)	800x480	800x600	1024x768		1280x1024	
Touch Technology	Analog resistive (4 wires)		Analog resistive (5 wires)			
Touch output	RS232 + USB					
USB frontal IP66 / USB rear (2.0)	1 x					
Green Led Power ON	1 x					
VGA/DVI-I * / S-Video / Video composite	1 x (* digital signal only single-link)					
External dimensions (W/H/D) (mm)	228x155x 66,7	250x190x 66,7	336x256x 56,7	425x300x 57,2	446x346x 59,7	508x384x 64,2
Cut-out dimensions (W/H) (mm)	219x145	241x180	321x240	393x275	426x326	477x353
Power supply (Vdc)	18...30 max 50W					
Power consumption (W)	30		35		45	
Protection degree (front)	IP 66					
Operating temperature (°C)	0...50 (non condensing)					
Storage temperature (°C)	-20+65					
Humidity	90% (non condensing)					
Weight (kg)	2,2	2,6	4,0	6,0	7,5	9
Certifications	CE / Atex 2014/34/UE directive Group II Category 3 G D Zone 2/22 Environmental EN60068-2-6/27/30 / Immunity EN61000-6-2 Emission EN61000-6-4					