



Esaware Web Panel

Browser-based efficient control

EW107BD with Android

	EW107BD2SP	EW107BD3SP	EW107BD5SP
Display Size	7"		
Display Technology	TFT		
Display Colors	16 M		
Display Backlight	LED		
Display Brightness (cd/m ²)	500		
Display Resolution (pixel)	1024 x 600		
Backlight Life (hours)	50 K		
Touch Technology	Capacitive		
Processor	ARM Cortex A9 Quad-Core		
RAM	2 GB DDR3L		
Flash	8GB		
Browser	Chrome/ WebView (fullscreen)	Chrome/ Microbrowser	Automation Browser
Ethernet Port	1 x 1 GB + 1 x 10 / 100 Mb		
USB Port	2 x vers. 2.0		
Serial Port	1 X RS232/485		
Expansion Slot	1 x MINI PCI express		
Cardbus slot	1 x SDHC		
Power Supply (Vdc)	12 - 32		
Consumption (W)	7		
Operating Temperature (°C)	-10 ... + 50 (non condensing)		
Storage Temperature (°C)	-20 ... + 65		
Humidity	<90% (non condensing)		
External dimensions(W/H/D) (mm)	192 x 132 x 32		
Cut-out dimensions (W/H) (mm)	185,0 x 125,0		
Weight (kg)	0.5		
Protection degree (front)	IP 66		
Certifications	CE / EN60068-2-6 / EN60068-2-27 / Humidity EN60068-2-30		
Display Technology	TFT		



EW110BD with Android

	EW110BD2SP
Display Size	10,1"
Display Technology	TFT
Display Colors	16 M
Display Backlight	LED
Display Brightness (cd/m ²)	350
Display Resolution (pixel)	1280 x 800
Backlight Life (hours)	30 K
Touch Technology	Capacitive
Processor	ARM Cortex A9 Quad-Core
RAM	2 GB DDR3L
Flash	8GB
Browser	Chrome / WebView (fullscreen)
Ethernet Port	1 x 1 GB + 1 x 10 / 100 Mb
USB Port	2 x vers. 2.0
Serial Port	1 x RS232 / 485
Expansion Slot	1 x MINI PCI express
Cardbus slot	1 x SDHC
Power Supply (Vdc)	12 - 32
Consumption (W)	24
Operating Temperature (°C)	-10 ... + 50 (non condensing)
Storage Temperature (°C)	-20 ... + 65
Humidity	<90% (non condensing)
External dimensions(W/H/D) (mm)	269,3 x 187,3 x 45
Cut-out dimensions (W/H) (mm)	255,5 x 173,5
Weight (kg)	1,1
Protection degree (front)	IP 66
Certifications	CE / EN60068-2-6 / EN60068-2-27 / Humidity EN60068-2-30



EW115BD with Android

	EW115BD2SP	EW115BD5SP
Display Size	15,6"	
Display Technology	TFT	
Display Colors	16 M	
Display Backlight	LED	
Display Brightness (cd/m ²)	300	
Display Resolution (pixel)	1366 x 768	
Backlight Life (hours)	50 K	
Touch Technology	Capacitive	
Processor	ARM Cortex A9 Quad-Core	
RAM	2 GB DDR3L	
Flash	8GB	
Browser	Chrome / WebView (fullscreen)	Automation Browser
Ethernet Port	1 x 1 GB + 1 x 10 / 100 Mb	
USB Port	2 x vers. 2.0	
Serial Port	1 x RS232 / 485	
Expansion Slot	1 x MINI PCI express	
Cardbus slot	1 x SDHC	
Power Supply (Vdc)	12 - 32	
Consumption (W)	24	
Operating Temperature (°C)	-10 ... + 50 (non condensing)	
Storage Temperature (°C)	-20 ... + 65	
Humidity	<90% (non condensing)	
External dimensions(W/H/D) (mm)	416,5 x 226,5 x 45	
Cut-out dimensions (W/H) (mm)	402,5 x 251,5	
Weight (kg)	3,7	
Protection degree (front)	IP 66	
Certifications	CE / EN60068-2-6 / EN60068-2-27 / Humidity EN60068-2-30	