



	<b>XV715</b>
Display Size	15"
Display Technology	TFT
Display Colors	262 K
Display Backlight	LED
Life (min. at 25°C)	50 K
Display Resolution (pixel)	1024 x768
Touch screen type	Analog resistive (5 wires)
CPU fanless	Intel ATOM Dual Core N2800 1,86 GHz
Chipset	Intel NMIO
Graphics embedded	Intel® GMA 3650
DMI	2,5 GT/s
RAM	Up to 4 GB DDR3 DIMM 204 pin
Removable HDD / SSD / mSATA (opt.)	Min. 500 GB SATA 2,5" / SSD 16 GB / mSA TA 32 GB
Compact Flash Slot Internal (opt.)	1 x
Compact flash Slot External (opt.)	1 x
RS232 serial port	1 x
RS485 serial port	1 x
USB on front (2.0) IP66	1 x
USB on rear (2.0)	2x
Green LED on front	1 x
Mini PCIe	1 x
Wi-Fi card (opt.)	miniPCIe x 1
Video port	1 x VGA
Ethernet port RJ45	2 x Ethernet 10/100/1000 Mbit Intel 82574
External (WxHxD) (mm)	425 x 300 x 77 (mm)
Back-up with battery	1 x
Power supply (Vdc)	18 ... 30 max 85W
Power consumption (W) (24 Vdc - basic config)	43
Protection level	IP 66 on front/ IP 54 on rear
Operating temperature (°C)	0 ... +50 (non condensing)
Storage temperature (°C)	-20 ... +65
Humidity	90% (non condensing)
Weight (kg)	7,5
Certifications	CE/ Environment EN60068-2-6/27/30 / Immunity EN 61000-6-2 / Emissions 61000-6-4
Operating system (32 bit)	WIN7 - WEST - WES 2009 - XP Pro for Embedded