



# Esaware Industrial Monitor

Innovative design. Elegant technology.

	EW315	EW322
Display Size	15,6"	21,5"
Display Technology	TFT	
Display Coloros	16,7 M	
Contrast	500:1	
Viewing Angle (H-V)	85/85/80/80	89/89/89/89
Display Resolution (pixel)	1366x768	1920x1080
Backlight life (hours)	50 K	
Touch Technology	Resistive (5 wires) / Capacitive (PCT 10 touches)	
Bezel / Chassis	Aluminum - PTFE no-sticking coating / Sheet Steel	
Front USB	1x USB 2.0 type A -rear 1x USB type B	
Rear touch outputs	1x USB 2.0 type B - 1x RS232 sub-din 9 pins	
Video input	DVI-D + VGA	
Power Supply (Vdc)	18 ... 30	
Consumption (W)	20W	30W
Operating temperature (°C)	0 ... +50 (non condensing)	
Storage temperature (°C)	-20 ... +65	
Humidity	<85% (non condensing)	
External dimensions (W/H/D) (mm)	437x286x58	572x363x61
Cut-out dimensions (W/H) (mm)	422,5x271,5	554,5x345,5
Weight (kg)	5	9,5
Protection degree (front)	IP 66	
Certifications	CE/ EN61000-6-2 / EN61000-6-4 / EN6008-2-6/27/30 ATEX 2014/34/UE directive Group 3 G D Zone 2/22	
External dimensions (W/H/D) (mm)	437x286x58	572x363x61
Cut-out dimensions (W/H) (mm)	326x227	554,5x345,5
Weight (kg)	4,5	10,5
Protection degree (front)	IP 66	
Certifications	CE / EN61000-6-2 / EN61000-6-4 / EN60068-2-6 / EN60068-2-6/27/30 / EAC ATEX 2014/34/UE directive Group II Category 3 G D Zone 2/22	