



Stainless Steel Industrial Monitor

Endurance and reliability

	XM7W7	XM712	XM715	XM719
Display Size	7" wide	12,1"	15"	19"
Bezel inox V2A	6mm thickness			
Technology	TFT 262 K colors		TFT 16,2 M colors	TFT 16,7 M colors
Display Backlight	LED			
Brightness cd/m2	500	370	350	400
Contrast	600:1		700:1	1000:1
Viewing Angle (H-V)	70-60	140-120		170-170
Lamp life (min at 25°C)	50 K			
Resolution (pixel)	800x480	800x600	1024x768	1280x1024
Touch Technology	Analog resistive (4 wires)		Analog resistive (5 wires)	
Touch output	RS232 + USB			
USB frontal IP66 / USB rear (2.0)	None			
Green Led Power ON	None			
VGA/DVI-I * / S-Video / Video composite	1 x (* digital signal only single-link)			
External dimensions (W/H/D) (mm)	228x155x 66,7	336x256x 56,7	425x300x 57,2	508x384x 64,2
Cut-out dimensions (W/H) (mm)	219x145	321x240	393x275	477x353
Power supply (Vdc)	18...30 max 50W			
Power consumption (W)	30		35	45
Protection degree	IP 69K front 7"/12,1" - IP66 front 15"/19"			
Operating temperature (°C)	0...50 (non condensing)			
Storage temperature (°C)	-20+65			
Humidity	90% (non condensing)			
Weight (kg)	3	5	7	10,5
Certifications	CE / Atex 2014/34/UE directive Group II Category 3 G D Zone 2/22 Environmental EN60068-2-6/27/30 / Immunity EN61000-6-2 Emission EN61000-6-4			