



EW327

Industrial Monitor

Control buttons	OSD control buttons on back to adjust contrast and brightness
External (W x H x D)	396.5mm x 657.5mm x 58 mm (15.61" x 25.88" x 2.28")
Cut out (W x H)	380.5mm x 641.5mm (14.98" x 25.25")
Material	Front: Aluminum - magnesium alloy anodizing ; Back: Metal paint
Installation	Embedded
Power supply	DC 24V
Power	30W
Video ports	VGA & DVI
Net weight	9KG
Size	27" Full HD TFT
Resolution	1920 x 1080
Color	16.7MB
Display (W x H)	336.15mm x 597.6mm (13.23" x 23.53")
Back light	LED
Pixel pitch	0.311 x 0.311
Brightness	300cd/ m
Contrast	3000 : 1
View	(L)150 / (R)150 / (U)150 / (D)150
Type	Multi capacitive
Transmittance	> 85%
Touch signal	USB
Working temperature	-0~50°C (-32~122°F)
Storage temperature	-20~60°C (-4~140°F)
Humidity	5~95%
Working vibration	SSD applied: 1.5 Grms, IEC 60068 -2-64, random, 5 ~ 500 Hz, 1 hr/axis
Working shock	SSD applied: 10 G, IEC 60068 -2-64
EMC	CE/ FCC Class A
IP	IP65 front