



Rugged Tablet

LUMIA708 CH/QM

LUMIA708CH11W00		
Product Form	Type	Rugged Tablet
	Dimension	228*145*16.5mm
	Weight	715g
LCD	Screen Size	8"
	Resolution	800*1280
	Brightness	450Nit
TP	Touch Panel	Multipoints Capacitive, Glass+Glass, Rigidity: above 7H-Anti-scratch
Camera	Front	2.0MP
	Rear	5.0MP
Speaker	build in	Embedded 8Ω/0.8W waterproof speakerx 1
Mic	build in	Sensitivity:-42db, output resistance2.2kΩ
Battery	Type	build in polymer li-ion battery
	Capacity	3.7V/8500mAh
	Endurance	8Hrs
CPU	Type	Intel Cherrytrail Z8350
	Speed	1.44Ghz-1.92GHz
RAM	LPDDR3	4GB
Disk	Emmc	64GB
G_sensor	build in	Gravity acceleration sensor
WIFI	WIFI module	WIFI 802.11(a/b/g/n/ac) Frequency 2.4G+5.8G dual band WIFI intel 3165D2WG
Bluetooth	build in	BT4.2 (BLE) class1 transmission distance: 10m
4G	build in	EC25 LTE FDD: B1/B3/B7/B8/B20/B28A WCDMA: B1/B8 GSM: B3/B8
GPS	build in	U-blox NEO-7 Support :GPS; Capture sensitivity: -160 dBm; Cool Start Time: <50second, Hot start time: <28seconds, frequency: 0.25 Hz ... 10 MHz (configurable)
TF slot	Extensive External Memory	support TF x1 max: 128G
USB Interface	Extend external memory and data transfer	USB2.0*1 (Host)



Earphone Jack	Audio Output	ϕ3.5mm standard earphone jack x1
DC Jack	Power	DC 5V 3A 3.5mm Power connector
HDMI	Video Output	HDMI 1.4a Type C x1
Docking connector	pogo Pin	12pin Pogo Pin x1
Power Adaptor	Standard	AC100V ~ 240V、50Hz/60Hz output DC 5V/3A
Operating System	OS version	Windows 10 IoT English
Certification	IP67	
	CE NB	
	MIL-STD-810G	
	Battery	UN38.3, MSDS,IEC62133
	Drop Height	1.2m
	Operate Temperature	'-10 °C to 50 °C
	Store Temperature	'-30 °C to 70 °C
	Humidity	Humidity: 95% Non-Condensing

LUMIA708QM11A00		
Product Form	Type	Rugged Tablet
	Dimension	228*145*16.5mm
	Weight	715g
LCD	Screen Size	8"
	Resolution	800*1280
	Brightness	450cd/m ²
TP	Touch Panel	Multipoints Capacitive, Glass+Glass, Rigidity: above 7H-Anti-scratch
Camera	Front	5.0MP
	Rear	13MP
Speaker	build in	Embedded 8Ω/0.8W waterproof speakerx 1
Mic	build in	Sensitivity:-42db, output resistance2.2kΩ
Battery	Type	build in polymer li-ion battery
	Capacity	3.7V/8500mAh
	Endurance	6Hrs
CPU	Type	Snapdragon MSM8953 (8core)
	Speed	2.0GHz
RAM	Memory	4GB/ LPDDR3
Disk	EmmC	64GB
Indicator light	build in	Indicator light of charge, red light will flash when device has low power. red long light when charging, green long light when full power
L-Sensor	Built-in	light Sensor *1



Compass	Built-in	Compass Sensor *1
Gyro Sensor	Built-in	Gyro Sensor *1
G_sensor	Built-in	Gravity acceleration sensor
WIFI	WIFI module	WIFI 802.11 b/g/n/a/ac frequency 2.4G+5G dual band WIFI,
Bluetooth	build in	BT4.1(BLE)
2G/3G/4G	build in	CMCC 4M : LTE B1,B3,B5,B7,B8,B20,B38,B39,B40,B41 WCDMA 1/2/5/8 GSM 2/3/5/8
GPS	build in	support:GPS+Glonass;Capture sensitivity:-140 dBm ; Cool Start Time : <50 秒, Hot start time : <5 秒, GPS frequency : 1575.42MHz, Glonass frequency:1602MHZ
TF slot	Extensive External Memory	x1 max : 128G
USB Interface		standard USB 2.0x1 、 type C x1 (data&charging)
Earphone Jack	Audio Output	φ3.5mm standard earphone jack x1
DC Jack	Power	DC 5V 3A φ3.5mm Power connector x1
HDMI	Video Output	HDMI 1.4a Type C x1
Extensive Slot	pogo Pin	12pin Pogo Pin x1
Operating System	OS version	Android 9.0 GMS
Certificate System	IP67	
	CE	Y
	MIL-STD-810G	Y
	Battery	UN38.3, MSDS,IEC62133
	Drop Height	1.2m composite wood floors, in operation status
	Operate Temperature	-10 °C to 50 °C
	Store Temperature	-20 °C to 60 °C
	Humidity	Humidity: 95% Non-Condensing