



Lumia Box IPC

Compact design. Multi-connectivity.

	LUMIA2MINI01350
Enclosure	Heavy alu extrusion chassisAlluminium heat-sink 1x power led1x HDD access led Lockable power connector Wall Mounting option
CPU fanless	Apollo lake N4200 processor
Chipset	Apollo lake single chip set
Video	HDMI: resolution up to 3840x2160VGA: resolution up to 2048 x 1536 (Synchronour or Aynchronous dual display) Intel HD graphics
RAM	4GB DDR3 SO-DIMM
Front I/O	USB: 2 x USB2.0 – 2*USB 3.0 Max support +5V/1A COM: 1 x RJ45 Port RS232 Infrared: 1 x IR infrared receiving port Audio: 1 x LINE OUT 1 x MIC
Rear I/O	Power supply: 1 x DC Video: 1 x VGA 1 x HDMI Ethernet: 2 x LAN
Ethernet controller	2 x Intel I211ATHigh Performance Gigabit LAN, RJ45 ports
Drives options	mSATA: SSD 128GB
Expansion bus	1 x Mini-PCIe slot
Operating system	W10 Enterprise LTSC 2019 64 bits
Operating temperature (°C)	-20 +60
Storage temperature (°C)	-40..+85
Humidity	< 95% (non condensing)
Weight (kg)	0,7
Power supply	12 ~ 19 VDC (Power adapter 230Vac/12Vdc Included)
Dimensions (WxHxD)	134mm x 126mm x 40,6mm
Protection degree	IP30
Certifications	CE, ROHS, FCC