



LUMIA Book

	IPC - Edge	IPC - Open
O.S.	W10 Enterprise LTSC 2019 64 bits	W10 Enterprise LTSC 2019 64 bits
Application Software	Kreo HMI	Open
Bezel / Chassis	Alluminium	
Processor	Intel Apollo Lake J3455 Intel Core i3-7100T Intel Core i5-7500T Intel Core i7-7700T	
Chipset	Apollo lake single chip set SoC	
GPU	Intel Gen.9 HD Graphics, HEVC/H265 High resolution	
RAM	4GB/8GB/16GB DDR4	
Mass storage	mSATA 128GB SSD mSATA 256 GB SSD (i7 model)	
Ethernet Port	2 x Intel i210-AT 1000Mbps RJ-45	
Video output	DVI-I 1920x1200 @60 Hz VGA 2560x1600 @60 Hz DP 4096x2304 @60 Hz	
COM Port	2 x RS-232 /422 /485 (DB9)	
USB Port	4 x USB3.0	
Audio	-	
Power supply	DC 12~24V input, 2 x 2-pin terminal	
Consumption (W)	10 – 80W	
Operating Temperature (°C)	-20°C ~ 60°C	
Storage Temperature (°C)	-40°C ~ 80°C	
Humidity	< 95% (non condensing)	
Dimensions (LxWxH)	Basic: 255mm x 152mm x 57.7mm KVM Transmitter: 255mm x 152mm x 70.8mm PoE 4xLAN switch: 255mm x 152mm x 70.8mm Exp slots: 255mm x 152mm x 112.7	
Weight	2~4KG	
Protection degree	IP30	
Certifications	CE, FCC compliant	
Switch	1 x Power switch 1 x AT/ATX select switch 1 x Clear/CMOS switch	