



LUMIA IPC Open

| | IPC - Open |
|--------------------------|--|
| O.S. | Windows 10 LTSC 2019 |
| Display Size | 10,1" (1280 x 800) 15,6" (1366 x 768) 21,5" (1920x 1080) 27" (1920 x 1080) |
| Display technology | TFT |
| Display Backlight | Led |
| Display Colors | 16M |
| Touch Technology | Capacitive |
| Bezel / Chassis | Alluminium |
| Processor | Celeron Quad Core J3455 – 2,3 GHz Intel Core i3-7100U 2,4 GHz Intel Core i5-7300U 3,5 GHz Intel Core i7-7600U 2,8 GHz |
| Chipset | SoC |
| GPU | Celeron Quad Core J3455 - HD Graphics 500 Intel Core i3-7100U – HD Graphics 620 – up to 1 GHz Intel Core i5-7300U – HD Graphics 620 – up to 1 GHz Intel Core i7-7600U – HD Graphics 620 – up to 1 GHz |
| RAM | Celeron Quad Core J3455 – 4GB DDR3L up to 8 GB DDR3L Intel Core i3-7100U 2,4 GHz Intel Core i5-7300U 3,5 GHz Intel Core i7-7600U 2,8 GHz 4GB up to 16 GB DDR4 |
| Mass storage | 256 GB SSD 512GB SSD 1TB SSD |
| Ethernet Port | Celeron Q.C.J3455 –2x1Gb RJ45 Intel I211AT Intel Core 7GEN - 2x 1Gb RJ45 Intel I210AT/I219LM |
| COM port | 1x RS232/RS485 |
| USB Port | Celeron QC J3455 – 2 x 3.1 Intel Core 7th GEN – 4 x 3.0 |
| Power Supply (Vdc) | 12 – 32V DC |
| Consumption (W) | 30W 10,1" 35W 15,6" 50W 21" 50W 27" |
| Operating temperature | 0 ... + 50 °C |
| Storage Temperature (°C) | -20 ... + 60 °C |
| Humidity | <90% (non condensing) |



| | |
|---------------------------------|---|
| External dimensions(W/H/D) (mm) | 10" panel 269 x 190 x 42 15" panel 402.4 x 251.7 x 45 15" vesa 382 x 230.8 x 80.7 21,5" panel 546.4 x 337.9 x 73 21.5" vesa 527.2 x 318.7 x 83 27" panel 669 x 406 x 73 27" vesa 648,4 x 385,5 x 83 |
| Cut-out dimensions (W/H)(mm) | 10" panel - 258.5 x 179.5 15" panel - 390 x 239 21" panel 531 x 323 27" panel 652 x 389 |
| Weight (kg) | 10" 5 15" 6,5 21,5 8KG 27" 10Kg |
| Protection degree | Panel – IP66 front Vesa – IP66 all around |
| Certifications | CE UL/ATEX/DNV |