



LUMIA IPC ARM

	ARM2xxxxxxxxxxx						
Size	15"	15.6"	18.5"	19"	21.5"	24"	27"
Resolution	1024x768	1366x768	1366x768	1280x1024	1920 x 1080	1920 x 1080	1920 x 1080
Ratio	4:3	16:9	16:9	4:3	16:9	16:9	16:9
Brightness(cd/m ²)	420	300	500	250	250	250	250
Protection	all IP65						
O.S.	Windows 10 IoT / Win11 / Linux						
Display	TFT						
Back light	LED (50000 hours)		LED (30000 hours)				
Color	16M						
Touch	PCAP						
CPU	J6412 2.0GHz, Intel Core i3-1115G4 3GHz, i5-1135G7 2.4GHz, i7-1165G7 2.8GHz						
RAM	4G, 8G, 16G, 32G DDR4						
Storage	128G, 256GB, 512GB, 1TB SSD						
RAID	RAID0 - RAID1						
TPM	Optional (N.A. default)						
USB front	2xUSB2.0 TypeA						
USB Rear	4xUSB2.0 TypeA						
ETH	4ETH (1xIntel i210AT + 1xi226AT + 2xIntel i211AT)						
Series Port	2xCOM (RS232/485)						
Video	1xHDMI						
Power (vDC)	24V DC (9~36V)						
Remote switch(vDC)	No						
Operation Tem. (°C)	0 ... + 50 °C						
Storage Tem. (°C)	-20 ... + 65 °C						
Humidity	<90% (non-condensation)						
Case material	Aluminum						
Button holes	Default 6holes, Max. 8 Holes (15" max. 6 holes)						
Buttons	Default(all 1NC1NO except Estop2NC), 1xEstop, 1xSelector, 1xStart, 1xStop, 1xReset, 1xUSB						
Arm Direction	Top-Down or Down-Top						
Hand holder	Keyboard support or Round bar						
Arm pipe	4460 (Alumium square pipe 44x60) or 48(Steeless circle pipe)						
Consumption (W)	36W	43W	41W	39W	45W	55W	65W
Net weight (Kg)	6,9	7	9,5	10	11	12,5	14
Certifications	CE						