



LUMIA Monitor ARM

	ARM3xxxxxxxxxxx						
Size	15"	15.6"	18.5"	19"	21.5"	24"	27"
Resolution	1024x768	1366x768	1366x768	1280x1024	1920 x 1080	1920 x 1080	1920 x 1080
Display	4:3	16:9	16:9	5:4	16:9	16:9	16:9
Brightness (cd/m ²)	400	500	250	250	250	250	250
KVM-Receive port	Optional (<=100m)						
Protection	all IP65						
LCD	TFT						
Back light	LED (50000hours)		LED (30000hours)				
Color	16M						
Touch	PCAP						
Front USB	2xUSB2.0 TypeA						
Rear USB	2xUSB2.0 TypeA						
Video ports	1xDVI, 1xVGA, 1xHDMI (KVM version: 1xHDMI+1xRJ45)						
Power (V DC)	24V DC (9~36V)						
Operation Temp. (°C)	0 ... + 50 °C						
Storage Temp. (°C)	-20 ... + 65 °C						
Humidity	<90% (non-condensation)						
Case material	Alumium						
Installation	4460 (Alumium square pipe 44x60) or 48(Steeless circle pipe)						
Arm Direction	Top-Down or Down-Top						
Hand holder	Keyboard support or Round bar						
Button holes	Default 6holes, Max. 8 Holes (15" max. 6 holes)						
Buttons	Default(all 1NC1NO except Estop2NC), 1xEstop, 1xSelector, 1xStart, 1xStop,1xReset, 1xUSB						
Consumption (W)	11W	18W	16W	15W	14W	20W	22W
Net Weight(Kg)	6,9	7	9,5	12,5	13,5	15	18
Certification	CE						